



LTV Series LED Seamless TV

Model: EID-AIO-PXX



INTRODUCTION

Seamless and flatness surface, adjustable brightness and color temperature, 100% image restoration that to bring you a HD visual experience.

FEATURES

Super Thin Wall Mounting

Flatness back cover with slim body, the thickness less than 10cm. Extremely light weight modules design to make a much more convenient installation work. The purposes of Lsemc LED TV is to offer a easy operation and facility.

Big View Angle

160° super wide viewing angle and 2-30 meters long visible distance to make every seat as VIP. High-definition pitcures without any reflect light and even in a long distance will see clearly.

Integrated design & concision style

Integrated with external devices, wireless screen transmission, remote video conference, and multi-win- dows splicing are available to maximize user's engagement.

Multi -function

Supports HDMI, USB ,WIFI, 4G signal input and PC ,Android,iso eg intelligent terminal management.LED TV support monitoring of temperature, humidity, brightness, etc. Automatic adjustment of display brightness also available.



SPECIFICATIONS

Parameter						
SPECIFICATIONS	LTV-120"	LTV-138"	LTV-165"	LTV-165"	LTV-220"	LTV-220"
TV Dimension(mm)	2560*1440*58	3000*1687.5*58	3600*2025*58	3600*2025*58	4800*2700*58	4800*2700*58
Pixel Pitch(mm)	P1.33	P1.56	P1.875	P0.9375	P2.5	P1.25
Resolution	1920*1080	1920*1080	1920*1080	3840*2160	1920*1080	3840*2160
Display Area(m ²)	3.6864	5.0625	7.29	7.29	12.96	12.96
Brightness(nit)	100cd~1200cd/sqm					
Refresh Rate(Hz)	Standard Refresh Rate:≤1920, High Refresh Rate:≤3840					
Power Consumption (Max/Ave)(W/display)	Average:150W/m ² ; Peak:800W/m ²					
Weight(kg)	33kg/m ²					
IP Rating	Front IP30, Back/IP65					
Gray Scale(Bit)	14					
Viewing Angle(H/V)	160°/160°					
Input voltage(V)	AC 100-240V					
Installation Method	Standing/Wall mounting					
Maintenance	Front					
Operating Temperature/Humidity(°C/RH)	-10~40/10%~85%					