



# AD Series LED Advertising Display

## Model: EID-DS-PXX



### INTRODUCTION

The LED advertising display integrates the world's leading small pixel pitch LED technology and intelligent android system.

Compared with the traditional heavy and bulky LED advertising displays, Isemc's screen is much lighter, slimmer, and more convenient as it can be set up, relocated and operated very simply.

### FEATURES

#### Intelligent Control

WIFI, 3G/4G, USB or HDMI wireless control etc, achieving both the synchronous and asynchronous control. Support centralized network management, remote control the display to carry out accurately targeted advertisement.

#### Diversification

Frame are available in various color. Hanging, standing and wall mounting are supported. Two way showing method- Horizontal and Verticality.

#### Convenient Use

Completely front service. Quick installation, simple operation, convenient maintenance, saving the cost greatly. Plug and play is available, automatic full play video source with extra operation. Easy and convenient.

#### Protections

24hour protection technology to realize functions such as, anti-collision, anti-humidity, anti-static, anti-radiation, wear-resisting, efficient heat dissipation.



## SPECIFICATIONS

	Specification	Parameter	Parameter	
Physical Parameter	Lamps	SMD 1515	SMD 2020	
	Pixel Pitch(mm)	1.8	2.571	
	Module Resolution	160*120	112*84	
	Cabinet Resolution	320*1080	224*756	
	Density(dots/unit)	345600	169344	
	Module Size(L*H*T mm)	288*216*6.2		
	Cabinet Size(mm)	576*1944*35		
	Cabinets Material	Aluminum		
	Modules Array	2*9		
	Weight Per Cabinet(kg)	35		
	Weight Per Modules(kg)	0.47		
	Optical Parameter	Grey Scale(bit)	14	
		Refresh Rate(Hz)	3840	
Drive Mode		1/30		
Brightness(nit)		600-1200 adjustable		
View Angle		H/160° V/160°		
Electrical Parameter	Input Voltage(V)	100-240		
	Current Frequency(Hz)	50/60		
	Max Power Consumption	654(unit)		
	Avg Power Consumption	218(unit)		
Application Environment	Storage Temp(°C)	-10 — +60		
	Working Temp(°C)	-10 — +50		
	Storage Humidity	10%-90%		
	Working Humidity	10%-90%		
	Protection Level	IP 30		
	Life Span(H)	100000		
	Installation Method	Hanging,Standing,Wall mounting		
	Maintenance Method	Front		