



75" Professional LED Backlit LCD Touch Screen Display

Model: CID-TSD-75



INTRODUCTION

75-inch interactive touch display adopts industrial-level LED full-array type backlight panel, of which the lifetime can be 100,000 hours because of its effective energy-saving. Built-in dual-point / multi-point infrared touch parts self-developed by iSEMC make touch much more sensitive and precise. Power button and the remote receiver is front installed to achieve a key energy-saving features and convenient remote control operation. 3.0cm ultranarrow frame design makes the body more elegant.

FEATURES

- Touch Screen applications of large sizes, 55", 65", 70", 84" 98";
- Professional grade LCD displays with LED back lit with lifespan 100,000hr;
- Aluminum frame with narrow bezel 28mm & bezel colors customized available;
- Chemically strengthened, anti-glare, anti-smudge glass options available;
- Shortcut key on the face glass for convenient use;
- PC expansion slots, easy to input/output the audio video signal;
- With the smart power energy saving function, the stand-by power consumption can be 0.5W;
- Supporting infrared Dual touch/Multi-touch;
- Designed for 24/7 usage.



SPECIFICATIONS

Model	CID-TSD-75
Size (inch)	75"
Backlight	LED
Contrast Ratio	1100:1
Response time	12ms
Pixel Pitch	0.429mm
Power Consumption	150W
Brightness (cd/m²)	450
Resolution	3840x2160
Signal Input	HDMI x4,VGA x1, Video x1,YPbPr x1
Color	10bit - 1070M
Viewing Angle	178°(CR≥10)
Aspect Ratio	16:9
Power Supply	100-240VAC, 50/60 Hz
Control method	RS232/RJ45,IR